

No Skidding®



266 Wildcat Rd, Toronto, ON M3J 2N5 Canada
Phone: (416) 667-1788 Fax: (416) 667-1783
sales@noskidding.com www.noskidding.com
or call us Toll Free at 1-800-375-0571

We warehouse within the U.S. for our U.S. customers

NSP No Skidding® ASSET Anti-Slip Sealer & Treatment

Anti-Slip Stain Sealer & Treatment for

- Grout
- Granite
- Saltillo Tile
- Brick
- Quarry Tile
- Marble
- Slate
- Travertine
- Ceramic Tile
- Limestone
- Flagstone
- Porcelain Tile
- Glazed Tile
- Terrazzo
- Concrete

Uses

- Kitchens
- Driveways
- Bathrooms
- Patios
- Showers
- Garages
- Health

Special Features

- Easy-to-Use
- VOC Compliant
- Non Flammable
- Interior & Exterior Use
- Retains Natural Color
- Water Base
- Oil Resistant
- Odorless

Product Description

ASSET penetrates into the surface and forms an invisible barrier that is resistant to moisture and stains, while allowing vapor to escape. It is not a surface coating and will not alter the natural look. ASSET can be used on interior and exterior applications.

DOES NOT CONTAIN PERFLUOROCTANE SULFONATE (PFOS); NO PERFLUOROC-TANOIC ACID (PFOA)

Slip Resistant when used as Recommended. ASSET increases the static coefficient of friction.

Test Data

Independent laboratory tests show ASSET out performs competitive products. Test results are available upon request for Staining, Static Coefficient of Friction, Tabor Abrasion, Surface Absorption, Freeze/Thaw and Vapor Transmission.

Sample Testing

Due to the differences of each material, several inconspicuous test patches should be completed to assure maximum performance. User must determine suitability of the product for their intended use.

ASSET is suitable for use on most natural stone surfaces both indoors and outdoors. Spreading rate will vary based on porosity of tile.

The action of walking is the transfer of body weight from one foot to another. If the walker weighs 160 lbs. then for the few seconds that the foot is on the tile, you are placing that amount of weight onto the surface. Fingers or an empty shoe cannot duplicate that weight and do not give a satisfactory result. We recommend placing the loose tile on the floor, if you are not testing on installed tile and then stepping onto the tile on the floor with the weight of your body and trying then to slide your foot on the surface.

Preparation: Apply onto a clean dry tile surface that is free of soil, grease, hard water deposits, sealers, waxes, varnishes or any other foreign material, film or coating that would prevent direct contact between the original tile surface and ASSET.

Pour ASSET into a plastic bowl. Take a folded piece of clean absorbent cotton towel (terry cloth), dip into the bowl of ASSET and wipe across the tile so as to soak the selected area well.



Allow ASSET to stand for about 5 minutes for maximum penetration into tile. All excess must then be removed by buffing surface with a clean, dry towel. This is important on polished, glazed and porcelain surfaces to avoid leaving a residue that would be visible on the tile. ASSET will be dry to the touch in 2-3 hours and may then be walked on. Do not wet or wash the surface for 12 to 24 hours to allow time for the full cure to take place. For optimum results the are should be kept dry and free from staining materials for 24 to 72 hours.

For application onto entire tile surface, see directions for use on ASSET label.

Protect Neighboring Surfaces

Always protect neighboring surfaces including wood, carpet, metal, landscaping and other non masonry surfaces.



Application Instructions

Read entire label and MSDS before using. This product should be used directly from container and is not under any circumstances to be thinned or diluted with anything before use.

Recommended method of application on larger floor areas.

The chemical components in ASSET do not adversely affect most surfaces. ASSET is very easy to apply. you may use a Lambswool applicator, pump up sprayer, clean towels or a light weight rayon mop. The general rule is to wet the surface with ASSET so that it gets very wet to your eye. Allow to stand 3-5 minutes and wipe or buff off the excess with a clean towel or carpet bonnet under a floor machine. Do not allow ASSET to dry or evaporate on the surface or a residue will appear. This residue can be removed by reactivating it with more ASSET and buffing immediately dry. For multiple applications allow to dry 1-3 hours minimum before applying second application. Two applications should be sufficient in even the worst situations.

Grout Sealing: Apply ASSET to all grout with a thin paintbrush. Any excess sealer that gets on the surface should be wiped off with a clean towel before it dries. On larger jobs, grout can be sealed by retreating the entire area including the tile or stone surface a second time. Be careful not to allow sealer to puddle or dry on presealed surfaces.

Floor Coating/Wax Removal: To remove existing coatings and/or waxes, use Flexstrip per the instructions.

Heavy Duty Cleaning: To remove lime and hard water deposits, efflorescence, rust, grease and other heavy dirt and grime use NS TAG Cleaner as directed. For a non-acid deep clean use OnGuard as directed.

Light Duty Cleaning: Use FlexClean as directed.

Existing Installations Surface Preparations

Surface must be dry and free of contaminants, including previously applied sealers, dirt, lime & hard water deposits, efflorescence, rust & other heavy dirt and grime.

Cure Time

ASSET will be dry to the touch in 1 - 3 hours and may then be put into service. For optimum results the area should be kept dry and free from staining materials for 24 - 72 hours.

Limitation of Liability: The great variation between environmental factors, possible surfaces and application techniques, and the lack of control we have over such matters, must affect our policies. Products are guaranteed not to be defective when applied and used in accordance with instructions. However, liability whether express or implied, is limited to replacement of product or refund of purchase price and cannot include liability for labor costs or consequential damages. Because of the variety of circumstances affecting each job, it is the user's responsibility to determine the suitability and safety of the product for any particular application. This limited warranty may not be modified or extended by manufacturer's representatives, distributors, or dealers.

We particularly recommend that users always test in small inconspicuous areas before application to the entire surface. If you are chemically sensitive, always test for personal tolerance.

No Skidding® products are in use around the world in hotels, warehouses, factories, shopping malls, public transit systems, airports, hospitals and senior care, office complexes, restaurants, day care, schools, fitness clubs, government and military facilities.

The most complete range of slip injury prevention products in the World.

Coverage

Coverage will vary depending on the density, porosity, texture, surface absorption, weather, time solution left on surface and application methods. Used as directed, ASSET will cover approximately 2000 sq.ft. / gal (3.785 liters).

Maintenance

Storage: Store ASSET in the original container, properly sealed to avoid contamination and evaporation. Stored at 77° F (40° C), ASSET will have a shelf life of 12 months. Do not allow to freeze.

Caution Keep out of Reach of Children
Warning: Detectable amounts of chemicals known to the State of California to cause cancer, birth defects or other reproductive harm may be found in this product.

ASSET may cause irritation of eyes and skin. Avoid contact and prolonged breathing. Use in a well ventilated area. Good ventilation means that fresh air is flowing in such a way as to feel a slight breeze. Open windows and use fans to circulate air. Continue to ventilate until vapors are eliminated. Exposure to high vapor concentration must be avoided. Inhaling the vapors can be harmful. Keep away from heat and open flames. Avoid prolonged contact with skin. Chemical resistant gloves should be worn at all times. Keep small children and pets out of area until product or surfaces has thoroughly dried. Refer to the MSDS for additional information.

No Skidding®



www.noskidding.com

266 Wildcat Rd, Toronto, ON M3J 2N5 Canada
 Phone: (416) 667-1788 Fax: (416) 667-1783
 sales@noskidding.com www.noskidding.com
 or call us Toll Free at 1-800-375-0571

We warehouse within the U.S. for our U.S. customers

* No Skidding® is a registered trademark of No Skidding Products, Inc., Toronto Canada