

**No Skidding®**



# NO SKIDDING COATINGS

266 Wildcat Rd, Toronto, ON M3J 2N5 Canada  
 Phone: (416) 667-1788 Fax: (416) 667-1783  
 sales@noskidding.com www.noskidding.com  
 or call us Toll Free at 1-800-375-0571

**We warehouse within the U.S. for our U.S. customers**

No Skidding® Products Inc. manufactures and distributes the most complete range of slip injury prevention products available anywhere. Our products include a full range of anti slip floor coatings, slip resistant treatments, floor care products, slip resistant tapes - grit, vinyl and resilient.

**Note:** Terms and conditions are subject to change without notice. E & O.E.

Please read detailed instructions & MSDS before using any No Skidding products.

**Limitation of Liability:** The great variation between environmental factors, possible surfaces and application techniques, and the lack of control we have over such matters, must affect our policies. Products

Available slip resistant and no profile. Commercial and Tough Industrial quality products, durable, most are chemical resistant. Please inquire for product specification data

**TRACTION GRANULES** - Granules include metal oxides, tempered glass, polymers, crushed rock, in a complete range of profiles for clear and colours.

Packing: 2 x 1 Gallon per Case & 5 Gallon pails  
 1 Gallon = 3.78 liters / 5 Gallons = 18.9 liters

are guaranteed not to be defective when applied and used in accordance with instructions. However, liability whether express or implied, is limited to replacement of product or refund of purchase price and cannot include liability for labor costs or consequential damages. Because of the variety of circumstances affecting each job, it is the user's responsibility to determine the suitability and safety of the product for any particular application. This limited warranty may not be modified or extended by manufacturer's representatives, distributors, or dealers.

**We particularly recommend that users always test in small inconspicuous areas before application to the entire surface. If you are chemically sensitive, always test for personal tolerance.**


Most paint coatings are approved by the U.S Dept. of Agriculture and Agriculture Canada. Paints include low odor and low V.O.C.

Available in: High Profile. Also Low Profile in Fine, Medium, Coarse & Regular (No Profile). Product Specification Data Sheets and MSDS are available on request. All One Part Epoxies are non-catalyzed.


## COMMERCIAL QUALITY COATINGS



ITEM NO.	DESCRIPTION
79015 Grey 79017 Green 79019 Tile Red 79020 Yellow 79021 Black 79022 Beige 79033 Sand	<p><b>EPICOTE EPOXY - Slip Resistant Floor Coating - Heavy Duty Pedestrian Grade High Profile With Integrated Traction Grit. ONE PART SYSTEM</b></p> <p>For interior use on wood, concrete or steel surfaces that require safe footing. Resistant to mild alkalis, acids and oils. Apply with brush or roller. Coverage approx. 150 sq. ft / gal. Clean up with Mineral Spirits. <i>2 Gal/Case.</i></p>
79023T Clear 76001T Grey 76003T Tile Red 76008T Yellow 76000T White 76012T Black	<p><b>EPICOTE EPOXY - Slip Resistant Floor Coating - Heavy Duty Pedestrian Grade Low Profile With Tempered Traction Granules. ONE PART SYSTEM</b></p> <p>For interior use on wood, concrete or steel surfaces that require safe footing. Resistant to mild acids, alkalis, grease, oil. Durable tough finish. Apply with brush or roller. Covers approx. 350 sq ft/gal. Clean up with Mineral Spirits. Traction granules are supplied in separate pre-measured packs and must be added to coating, available in fine or medium. <i>2 Gal/Case.</i></p>
79140 Clear 76001 Grey 76003 Tile Red 76008 Yellow 76000 White 76012 Black	<p><b>EPICOTE EPOXY - Finish Coat &amp; Sealer - One Part Hard Wearing &amp; Chemical Resistant. Regular No Profile Not Slip Resistant</b></p> <p>For use on floors, machinery, etc. For concrete factory floors and wooden gymnasium floors. Tough, durable and convenient, one component application. An economical concrete floor sealer and finish for industrial use in manufacturing operations, warehouses etc., a tough, durable, lustrous finish. For interior use on wood, concrete or steel surfaces. Resistant to acids, oil, alcohol, fruit juice, cleaners, and moisture. Recommended as a sealer on concrete to prevent dusting and deteriorating. Apply with brush or roller. Coverage: 400 sq ft/gal, one coat. On non porous surfaces.</p>
79WBC Clear 79WBG Grey 79WBW White	<p><b>EPICOTE EPOXY W.B. - Waterbase One Part Slip Resistant Floor Coating</b></p> <p>Low Profile. Safe, durable and suitable for food industry and where chemical solvents would be a concern. Non-flammable. For use on wood, steel, previously painted surfaces etc. Fast dry. Additional colors available to order. Coverage 300 sq ft/gal</p>
79QDC Clear 79QDG Grey 79QDW White	<p><b>EPICOTE EPOXY Q.D. - Quick Dry One Part Slip Resistant Floor Coating</b></p> <p>Low Profile. Solvent Base. Very rapid drying for getting the job done quickly. For use on wood, steel, previously painted surfaces. Glass fiber Additional colors available to order. Coverage 300 sq ft/gal. Indoors and outdoors use. Anti-Slip grit integrated into product. <i>4 Gal/Case.</i></p>



ITEM NO.	DESCRIPTION
<b>11930C Clear</b> <b>11930W White</b> <b>11930GGrey</b> <b>11930B Black</b> <b>11930Y Yellow</b>	<p align="center"><b>EPOXY SLIP RESISTANT TEXTURED AEROSOL SPRAY</b></p> <p>For use indoors and outdoors. A slip resistant epoxy spray that cures to a hard, textured finish. Adheres to fiberglass, wood, steel, concrete and other surfaces where a slip resistant finish is desired. Effective on steps, ramps, loading docks, bathtubs, shower floors, fire escape ladders, stair treads, pool surrounds, boat decks and around machinery. Self priming on most surfaces. Special nozzle helps to prevent blockage. Quick drying. Available in gallon cans. See Product 79QD. Additional colors available: <i>12 oz. Spray Cans 12/Case</i></p> 
<b>11940C Clear</b> <b>11940W White</b> <b>11940G Grey</b> <b>11940B Black</b> <b>11940Y Yellow</b>	<p align="center"><b>MARINE EPOXY SLIP RESISTANT TEXTURED AEROSOL SPRAY</b></p> <p>Specific to marine market. Suitable for boat decks and marinas. Covers 24 sq. ft. per aerosol. <i>12 oz. Spray Cans 12/Case</i></p>

**INDUSTRIAL QUALITY COATINGS AQUATUFF & EPO TUFF**  
are supplied in kits consisting of resin & cure. Prices are per full single gallons.

ITEM NO.	DESCRIPTION
<b>78001 Clear</b> <b>78002 White</b> <b>78003 Grey</b> <b>78007 Red</b> <b>78008 Black</b> <b>78009 Az. Blue</b> <b>78011 Safety Blue</b> <b>78013 Yellow</b> <b>78023 Sand</b>	<p><b>AQUA TUFF - 2 Part Waterbase Epoxy No Profile Not Slip Resistant.</b></p> <p>Chemical and abrasion resistant. Not affected by brake fluid. Ideal for garage service bays. Solvent free regular or slip resistant. Hard wearing. Resists aviation, gasoline and skydrol. May be applied to oil-stained floors. Coverage approx. 225 / 250 sq ft/gal. Clear 350 sq ft/gal per coat Additional colors available to order.</p> 
<b>78001T Clear</b> <b>78002T White</b> <b>78003T Grey</b> <b>78007T Red</b> <b>78008T Black</b> <b>78009T Az. Blue</b> <b>78011T Safety Blue</b> <b>78013T Yellow</b> <b>78023T Sand</b>	<p align="center"><b>AQUA TUFF - 2 Part Slip Resistant Waterbase Epoxy.</b></p> <p>Available With Traction Granules. Not affected by brake fluid. Ideal for garage service bays. Hard wearing. Resists aviation, gasoline and skydrol. May be applied to oil-stained floors. Colors Coverage approx. 225/250 sq ft/gal in colors. 300 sq. ft clear. Additional colors available to order.</p>
ITEM NO.	DESCRIPTION
<b>ES-83</b>	<p><b>EPO-TUFF ES-83 - 2 Part Slip Resistant Epoxy System</b></p> <p>2 gallon kit. For extreme wear conditions. Very heavy duty. 83% solids. Available in gray, tile red, black and white. Inquire about other colors No Profile. Suitable for factories, warehouses, parking garages, tow-motor traffic. Spreading rate up to 250 sq.ft / per gallon at 5 ml thickness. Also available with no profile.</p> 


<b>EWB-36</b>	<b>EWB-36 - Waterborne, No Profile</b> A high performance clear waterborne epoxy. Acrylic coating suitable for steel, concrete, wood, VCT, tile, etc. VOC compliant and gloss finish.	
<b>EWB-36T</b>	<b>EWB-36 - Waterborne, Slip Resistant</b> A high performance clear waterborne epoxy. Acrylic coating suitable for steel, concrete, wood, VCT, tile, etc. VOC compliant and gloss finish. Supplied with anti slip polymer aggregate.	
<b>AU-73</b>	<b>EPO-TUFF AU-73 2 Part Clear Aliphatic Urethane System - 1 gallon kit</b> A high build, high solids durable system that resists impact & and abrasion. Suitable for most interior/exterior surfaces.Exceeds EPA VOC requirements. Coverage is 300 sq. ft. pergallon at 5 ml thickness. Rapid Cure. <b>Slip Resistant.</b> Also available with no profile.	


## SLIP RESISTANT PAINT COATINGS VULCAN RUBBER RESIN

### ASK FOR DETAILED PRODUCT DATA SHEETS

Available Slip Resistant & No Profile, Durable, easy to use.

Chemical Resistant. Highly U.V Resistant. Recommended for outdoor & Indoor use.


ITEM NO.	DESCRIPTION	
<b>99002 Grey</b> <b>99003 Green</b> <b>99004 Tile Red</b> <b>99005 Yellow</b> <b>99006 Black</b> <b>99007 Han. Blue</b> <b>99011 White</b> <b>99013 Sand</b>	<b>VULCAN U.V. High Profile - Heavy Duty Pedestrian Grade</b> Slip Resistant Floor Coating. Contains heavy integrated traction grit. For interior and exterior use on wood, concrete or steel surfaces that require safe footing. Incorporates anti slip aggregates to the hazards of slipping areas. Resistant to weathering, abrasion and mild chemical. Ideal for around pools, steps, ramps, sidewalks, etc. ONE PART SYSTEM. Ideal for old or new concrete. Coverage approx.100 - 150 sq ft/gal. <i>2 Gal/Case.</i>	
<b>97008T Clear</b> <b>97005T Grey</b>	<b>VULCAN U.V. LOW PROFILE- Heavy Duty Pedestrian Grade</b> Slip Resistant Floor Coating - with tempered traction granules Resistant to UV light. Clear is non-yellowing. Crystal Clear. For interior & exterior use on wood, concrete or steel surfaces that require safe footing. ONE PART SYSTEM. For old or new concrete. Protects concrete against deicing damage, oil, grease & trade soils. Stops concrete dusting. Produces a seal that retards moisture in new concrete for full strength curing. Good chemical resistance to acids, alkalis & glycol. Coverage is approx. 350 sq ft/gal. Apply with brush or roller. Traction granules are supplied in separate pre-measured packs and must be added to coating available in fine, medium or coarse.	
<b>94010 Clear</b> <b>97005 Grey</b>	<b>VULCAN U.V. Regular No Profile - Heavy Duty Pedestrian Grade</b> finish Coat & Primer - One Part Hard - Wear & Chemical Resistant Coatings For use on floors, machinery, etc. Functions as both a sealer & finish coat on concrete, brick, metal, stone. Recommended for concrete floors, parking decks, ramps, bridges, entrances etc. Helps prevent concrete from dusting. Resistant to UV light, clear, is non yellowing, good chemical resistance to acids, alkalis and glycol. Can be top coated with many other finishes. Coverage is 400 sq ft/gal.	


ITEM NO.	DESCRIPTION
<b>97301 Light Gray</b> <b>97302 Red</b> <b>97303 Black</b> <b>97304 Brown</b> <b>97305 Beige</b> <b>97306 H. Blue</b> <b>97308 Yellow</b> <b>97309 White</b> <b>97313 Green</b>	<p align="center"><b>Super Acrylic High Profile Slip Resistant Coating</b></p> <p>#97300 Series is a tough, abrasive, anti-slip coating for a variety of interior and exterior applications. This product significantly reduces the chances of slipping, although this product cannot totally prevent the possibility of slipping. It is low odour and low VOC. Soap and water cleanup. <b>RECOMMENDED USES:</b> Suitable for use on walkways, steps, ramps, locker room floors, boat decks, and a variety of other interior and exterior concrete, wood and metal surfaces that have been properly prepared. This product is not for use in areas where it will be underwater; it is also not for use on garage floors or other areas of wheeled vehicle traffic. Coverage 100 - 150 sq ft/gal. <i>2 Gal/Case.</i></p> 

## VULCAN W.B WATERBASE

Rubber Resin Slip Resistant Paint Coating. These water base products have similar performance characteristics to Vulcan U.V. (Solvent Base) Low V.O.C. Environmentally approved. Rapid Recoatability. Very rapid curing. No odor, Non flammable. Chemical resistant. Water resistant. Very durable in all climates. Self priming. Excellent for exterior & interior use. Highly ultra-violet light resistant Available.

ITEM NO.	DESCRIPTION
<b>49102 Gray</b> <b>49103 Black</b> <b>49108 Yellow</b> <b>49113 Green</b> <b>49115 Brown</b>	<p align="center"><b>VULCAN W.B. - High Profile Slip Resistant</b></p> <p>Waterbased, moderate anti slip resistant coating. Designed for indoor or outdoor, on wood, metal and concrete surfaces. Resists abrasion and mild chemicals. Durable pedestrian grade soap and water cleanup. Spreading rate 100-125 sq. ft./gal. <i>2 Gal/Case.</i></p>

ITEM NO.	DESCRIPTION
<b>56101-1 Gray</b>	<p align="center"><b>Alkyd, URETHANE FORTIFIED - Slip Resistant Gray</b></p> <p>A tough, easy to apply one part coating. High Gloss. General purpose. Spreading rate 400 sq. ft. per gallon. <i>2 Gal/Case.</i></p> 

ITEM NO.	DESCRIPTION
<b>SDP-1</b> <b>SDB-1</b> <b>SDT-CB-1</b> <b>SDT-COB-1</b> <b>SDT-SG-1</b>	<p align="center"><b>Safe Deck</b></p> <p>Safe Deck is a semi-industrial, hardwearing 3 part acrylic system consisting of a primer, basecoat and color finish. Safe Deck has been especially formulated for use on sundecks, balconies, boat decks, steps, concrete areas, tennis courts, basement floors etc. <i>2 Gal/Case.</i></p> 

## SUNDRY PAINT PRODUCTS

ITEM NO.	DESCRIPTION
<b>61378</b>	<p align="center"><b>CERAMIC TILE PREP</b></p> <p>A simple method to prepare any ceramic or natural stone surface before the application of floor coatings. Use indoors and outdoors. Water based, minimal odor, not as aggressive as muriatic acid. For use on terrazzo slate, quarry tile, ceramic, before the application of a coating Improves adhesion. Coverage 400 sq ft/gal. <i>4 Gal/Case.</i></p>
<b>ASM 825</b>	<p align="center"><b>DIGITAL SLIP METER</b></p> <p>To measure co-efficient of friction on all hard surfaces. Calibrated to James Machine as per ASTM &amp; OSHA. Weighs 5 lbs (2.2 kg) Very robust &amp; portable. Heavy duty steel casing with carrying case.</p>