

No Skidding



266 Wildcat Rd, Toronto, ON M3J 2N5 Canada
Phone: (416) 667-1788 Fax: (416) 667-1783
sales@noskidding.com www.noskidding.com
or call us Toll Free at 1-800-375-0571

We warehouse within the U.S. for our U.S. customers

EPICOTE EPOXY

LOW VOC - INTERIOR & EXTERIOR FLOOR COATING

77300 SERIES



Description

No Skidding Epicote 77300 Series is a low VOC, heavy-duty, Solvent borne coating designed for use on interior or exterior concrete, metal, and wood surfaces. This one component product is epoxy and polyurethane modified for enhanced resistance to abrasion, repeated washing, marring and many chemicals such as grease, oil, alcohol, mild solvents, weak acids and alkalis. Available in a variety of gloss, ready-mixed colors, this finish is ideal for factory floors, warehouse, garage floors, showrooms, and service station floors as well as railings, catwalks, storage tanks, equipment and many other applications.

Surface Preparation

All surfaces to be painted must be clean, dry and free from dirt, grease, wax, oil, rust, mildew, chalk, soap residue, efflorescence, loose paint and any other foreign matter. New concrete or masonry surfaces should age at least 30 days old before being painted. Powdery concrete must be repaired to a sound surface before painting. Concrete that is smooth troweled or suspected of treatment with chemical "de-icers" should be etched with dilute muriatic acid and rinsed thoroughly with clean water before painting to promote bonding. Follow acid manufacturer's label directions for proper use and recommended protective equipment. Unsound or rotting wood must be replaced before painting. This coating may be applied directly to properly prepared bare metal. Glossy surfaces should be scuff sanded to promote the maximum adhesion of this product.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Product Characteristics

Anti slip when used with accompanying traction grit

Abrasion, chemical, corrosion resistant

High gloss

One component

Low VOC solvent borne

Multi-surface application

Interior and exterior application



Method Of Application

Stir thoroughly and apply without thinning by brush, roller, or spray at a rate of up to 400 sq. ft. per gallon. Square foot averages may vary depending upon surface texture and porosity. This product is dry to walk on or recoat in 24-36 hours under normal conditions. Cool temperatures, high humidity, heavy film thicknesses, or poor ventilation will extend drying times. Clean up equipment immediately after use with paint thinner or mineral spirits and dry for storage. Follow solvent manufacturer's label directions for use and recommended protective equipment.



Technical Data (Based on 77301 White)

Weight per Gallon.....	9.8 +/- 0.25 lbs/gal
Viscosity.....	65-75 KU
Gloss.....	85%+
Weight Solids.....	63% +/- 2.0
Volume Solids.....	51% +/- 2.0
Coverage.....	400 square feet per gallon
Dry Time (@77°F / 50% RH)	
Set-to-Touch.....	2-4 hours
Recoat/Light Duty.....	24-36 hours
Hard/Normal Use.....	48-72 hours
Flash Point (Setflash).....	104° F
VOC.....	<340 g/l (<2.8 lbs/gal)



Colors.....77300 - Clear, 77301 - White, 77302 - Black, 77303- Handicap Blue, 77305 - Light Gray, 77306 - Green, 77308 - Yellow, 77309 – Dark Gray, 77312 - Red, 77314 - Brown, 77315 - Beige

Available Container Sizes

5 Gallon and 1 Gallon Containers

Read and fully understand label and Material Safety Data Sheet before using. Use in adequately ventilated areas. Extinguish all flames and pilot lights. For Professional Use Only

The information and data given herein are based upon tests and reports considered reliable and believed to be accurate. However, due to circumstances beyond our control including but not limited to surface preparation, application technique, substrate and curing conditions, no guarantee of duplicate

PLEASE READ AND FULLY UNDERSTAND LABEL AND MSDS BEFORE USING.

Important: Seller's and manufacturers only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for the intended use, and the user assumes all risk and liability whatsoever in connection therewith. No statement of recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of the seller and manufacturer. Buyer assumes all risk and liability associated with disposal.

No Skidding® products are in use around the world in hotels, warehouses, factories, shopping malls, public transit systems, airports, hospitals and senior care, office complexes, restaurants, day care, schools, fitness clubs, government and military facilities.

The most complete range of slip injury prevention products in the World.



266 Wildcat Rd, Toronto, ON M3J 2N5 Canada
 Phone: (416) 667-1788 Fax: (416) 667-1783
 sales@noskidding.com www.noskidding.com
 or call us Toll Free at 1-800-375-0571

We warehouse within the U.S. for our U.S. customers
 * No Skidding® is a registered trademark of No Skidding Products, Inc., Toronto Canada