

No Skidding®



266 Wildcat Rd, Toronto, ON M3J 2N5 Canada
Phone: (416) 667-1788 Fax: (416) 667-1783
sales@noskidding.com www.noskidding.com
or call us Toll Free at 1-800-375-0571

We warehouse within the U.S. for our U.S. customers

NSP No Skidding®

EPO-TUFF HEAVY DUTY SLIP RESISTANT FLOOR COATING SYSTEM

High-Gloss, Slip & Abrasion-Resistant Protection For Floors

No Skidding® high-performance coatings team up to create The Epo-Tuff System. A durable, easy-to-apply system that protects and slip proofs concrete and other hard floors indoors and out.

Epo-Tuff ES-83 High Solids Epoxy

The first coat in the system is Epo-Tuff ES-83 Epoxy (83% Solids), which provides a tough, dense film that's particularly effective in protecting concrete in moist, corrosive environments. A proprietary blend of epoxy resins, ES-83 protects concrete far better than ordinary epoxies. Its 900 psi adhesion exceeds the cohesive strength of the concrete itself, and its resistance to water vapor penetration is unsurpassed. One coat is equivalent to 3 coats of conventional quality paint.

Epo-Tuff AU-73 High Build Polyurethane

Epo-Tuff AU-73 (73% Solids) provides a glossy, flexible finish that resists chemicals, scuffing and abrasion.

Conventional polyurethanes produce a dry-film thickness of only about 2.5 mils in one coat, but a single coat of AU-73 builds to twice that thickness. Conventional polyurethanes are primarily decorative, they can't stand up to abrasion and abuse-but AU-73 is so flexible and resilient that it can withstand four times more direct impact. AU-73 also retains color and gloss better than most polyurethanes and ten times better than epoxies.

Easy to Apply, Simple to Maintain

High performance isn't the only Epo-Tuff benefit, it is also convenient to use. Both ES-83 and AU-73 are VOC compliant, and both deliver maximum high build without sophisticated application equipment or special techniques. Any qualified commercial painting contractor or maintenance team can apply just by brushing or rolling.

The coated floor is remarkably durable and easy to maintain. It stands up to steam, harsh detergents and most industrial chemicals and still keeps shining.

With ES-83 underneath, providing unequalled adhesion and barrier properties, and AU-73 on top, adding enhanced chemical resistance and a safe slip resistant resilient finish, this is an unbeatable combination in just two coats.

PLEASE READ AND FULLY UNDERSTAND LABEL AND MSDS BEFORE USING.

Important: Seller's and manufacturers only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for the intended use, and the user assumes all risk and liability whatsoever in connection therewith. No statement of recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of the seller and manufacturer. Buyer assumes all risk and liability associated with disposal.

No Skidding® products are in use around the world in hotels, warehouses, factories, shopping malls, public transit systems, airports, hospitals and senior care, office complexes, restaurants, day care, schools, fitness clubs, government and military facilities.

The most complete range of slip injury prevention products in the World.



No Skidding®

www.noskidding.com

266 Wildcat Rd, Toronto, ON M3J 2N5 Canada
Phone: (416) 667-1788 Fax: (416) 667-1783
sales@noskidding.com www.noskidding.com
or call us Toll Free at 1-800-375-0571

We warehouse within the U.S. for our U.S. customers

* No Skidding® is a registered trademark of No Skidding Products, Inc., Toronto Canada

E.&O.E.

