

**No Skidding®**



266 Wildcat Rd, Toronto, ON M3J 2N5 Canada  
Phone (416) 667-1788 Fax (416) 667-1783  
sales@noskidding.com www.noskidding.com  
or call us Toll Free at 1-800-375-0571  
We warehouse within the U.S. for our U.S. customers

# PASS - POROUS SURFACE ANTI SLIP SEALER FOR EXTERIOR & INTERIOR FLOORS Product #8901

## Description

No Skidding® **PASS** - Porous Anti Slip Surface Sealer is a water-based indoor/ outdoor hard surface sealer that provides superior resistance to grease, moisture, solvents and other foreign materials, for concrete, brick, terra cotta, pavers, saltillo tiles, as well as many unglazed ceramic tiles. **PASS** can achieve a high gloss in as little as 2 coats.

## Product Features / Benefits

- With optional micro traction booster for added slip resistance as required.
- Easy to Apply/ Saves time, labor and reduces training requirements.
- UV Resistant / Great for outdoors including areas with direct sunlight.
- Low odor, fast drying.
- Eliminates need for surface etching thereby saving time and labor.
- Forms a wear resistant barrier on surface subject to grease, oil and soiling.
- Water resistant.
- Does not whiten or “peel-off” surfaces.



## Recommended For

Indoors and outdoors: Swimming pool decks, stamped unsealed patterned concrete, office buildings, shopping malls and plazas, supermarkets and retail stores, schools, warehousing, etc.

## Directions For Use

Floor Preparation for all Interior / Exterior Surface Applications: Remove all grease, oil and other foreign materials from the surface with No Skidding® Flexclean or No Skidding® On Guard. If previous coatings are present, remove the coating with the appropriate stripper. Rinse the surface thoroughly and allow the surface to fully dry prior to application of **PASS**.

Application: Apply **PASS** using a lambs wool applicator, paint roller or a rayon finish mop. The first coat should be applied using a thin even coating on surface. Allow a minimum of 45 minutes drying time before the application of additional coats.

Optional: Gently shake material to ensure integrated micro traction is evenly dispersed within container before using.

Routine Maintenance: Damp mop floors with mop & bucket or clean with an automatic scrubber using Flexclean and follow label direction. For areas that require heavy cleaning or degreasing, use On Guard Degreaser following the label directions. Rinse surface with water after cleaning.

**Specifications**

Color .....Opaque liquid  
Odor ..... Typical acrylic  
pH ..... 8.25 ± 0.25  
Drying Time (minutes) .....30  
Coverage (sq. ft. /gal) ..... up to 2,000  
Slip Resistant A.S.T.M. D-2047 ..... Yes

Freeze Thaw Stable ..... Yes (3 cycles)  
Detergent Resistant ..... Yes  
Leveling ..... Excellent  
Water Resistance ..... Excellent  
Black Mark Resistant ..... Excellent  
Scuff Resistance ..... Excellent  
Resistance to Soiling ..... Excellent  
Gloss Retention ..... Excellent  
Immediate Wet Look Gloss ..... Very Good



Shelf Life ..... 1 year minimum in original Container

**SAFETY INFORMATION**

**CAUTION:** MAY BE HARMFUL IF SWALLOWED. MAY CAUSE SKIN IRRITATION. KEEP OUT OF REACH OF CHILDREN. Avoid contact with eyes. Do not ingest. If ingested, may cause severe gastric distress and blockage.

**FIRST AID:**

**For Eyes:** Flush thoroughly with water for at least fifteen minutes. If irritation persists seek medical attention.

**For Skin:** wash thoroughly with soap and water. If irritation persists seek medical attention.

**If Ingested:** Do not induce vomiting. Give large quantities of water. Seek medical attention. Never give anything by mouth to an unconscious person.

Meets or exceeds 0.5 coefficient of friction as measured by James Machine Methodology ASTM Method D 2047-82. KEEP FROM FREEZING. FOR PROFESSIONAL USE ONLY.

**READ MATERIAL SAFETY DATA SHEET BEFORE USING THIS PRODUCT.**

**Limitations**

The technical data and suggestions for use in this product data sheet are currently correct to the best of our knowledge, but are subject to change without notice. Because application and conditions vary, and are beyond our control, we are not responsible for results obtained in using this product, even when used as suggested. The user should conduct tests to determine the suitability of the product for the intended use under then existing conditions. Any liability we may have with respect to a product or its use (including liability for breach of warranty, strict liability in tort, negligence or otherwise) is limited exclusively to replacement of the product or refund of its price. Under no circumstances are we liable for incidental and consequential damages.

**PLEASE READ AND FULLY UNDERSTAND LABEL AND MSDS BEFORE USING.**

**Important:** Seller's and manufacturers only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for the intended use, and the user assumes all risk and liability whatsoever in connection therewith. No statement of recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of the seller and manufacturer. Buyer assumes all risk and liability associated with disposal.

No Skidding products are in use around the world in hotels, warehouses, factories, shopping malls, public transit systems, airports, hospitals and senior care, office complexes, restaurants, day care, schools, fitness clubs, government and military facilities.

**The most complete range of slip injury prevention products in the World.**



266 Wildcat Rd, Toronto, ON M3J 2N5 Canada  
Phone: (416) 667-1788 Fax: (416) 667-1783  
sales@noskidding.com www.noskidding.com  
or call us Toll Free at 1-800-375-0571

**We warehouse within the U.S. for our U.S. customers**  
\* No Skidding® is a registered trademark of No Skidding Products, Inc., Toronto Canada