



266 Wildcat Rd., Toronto, ON M3J 2N5
 Tel: (416) 667-1788 • Fax: (416) 667-1783
 sales@noskidding.com • www.noskidding.com

TECHNICAL DATA SHEET

NO SKIDDING® ANTI-SLIP MAINTAINER A.S.M. No. 72378

DESCRIPTION

ANTI-SLIP FLOOR CLEANER & TREATMENT FOR POROUS SURFACES - REDUCES POTENTIAL FOR SLIPS AND FALLS AND INCREASES SLIP RESISTANCE.

No Skidding® Anti-Slip Maintainer A.S.M. is formulated for use on porous floors such as quarry, unglazed ceramic tile and concrete floors. It is used full strength or diluted to remove both grease deposits and silica stains while restoring the stone floor surface to its original slip-resistant condition. Ideally suited for the Food Service Industry on kitchen floors and prep areas; restaurants, commissaries, fast food and food service operations. Industrial applications in manufacturing facilities, school shower rooms and anywhere costly Slips & Falls are a problem.

- UL listed for Slip-Resistance for dry (COF)
- ANSI A137.1 for slip-resistance for wet (DCOF)

FEATURES AND BENEFITS

- Increases Slip-Resistance
- Concentrated and Easy to Use, Saves labor.
- Two-in-one
- Non-hazardous, Non-corrosive, Septic Tank Safe
- Apply by Brush, Sprayer, Foamer or Automated Equipment
- Reduces Potential for Slip and Fall Accidents
- Reduces Costs
- Removes silica and hard water stains, grease & oil from floor pores and grout lines

TECHNICAL DATA

| PROPERTY | VALUES |
|------------------------------|--|
| pH | 2.0-3.0 |
| Specific Gravity | 1.03 |
| Viscosity | Water Thin |
| Melting point/freezing point | No information available |
| Flash point | Above 200°F |
| Boiling point/boiling range | No information available |
| Evaporation rate | Same as water |
| Upper Flammability limit | No information available |
| Lower Flammability limit | No information available |
| Vapor pressure | No information available |
| Vapor density | No information available |
| Water solubility | Soluble in water |
| Partition coefficient | No information available |
| Autoignition temperature | No information available |
| Decomposition temperature | No information available |
| Density Lbs./Gal | 8.6 |
| VOC Content (%) | 2.6% VOC CARB COMPLIANT for product category |

SURFACE PREPARATION

- Restoration “Shock” Slip Treatment Procedure (As Needed)
- Use A.S.M. Slip Resistant Treatment full strength whenever floor surface is out of control with heavy stains or grease buildups. NOTE: On new floors or lightly soiled floors, SHOCK cleaning procedure is not recommended, use Daily Slip Treatment Procedure. Pretest glazed tile floors before using.

APPLICATION METHOD FOR FLOORS

Floor Maintenance Slip Treatment and Cleaning Procedures:

Daily Cleaning: Dilute 2 to 4 oz. A.S.M. per gallon of water.

Weekly Heavy Scrub: Dilute 12 oz. A.S.M. per gallon of water.

Monthly Heavy Scrub: Dilute 48 oz. A.S.M. per gallon of water.

Follow these steps for each of the above cleaning procedures:

1. Apply product liberally, evenly and directly to floor. Leave product on the floor for 5 minutes to penetrate soil.
2. Scrub floor with deck brush, floor machine with appropriate pad / brush. Pay special attention to grout lines and heavily soiled areas.
3. Rinse thoroughly with clean water. When used in Federally inspected food processing areas, A.S.M. must be followed by a potable water rinse.
4. Squeegee remaining water and residue to floor drains. Use a wet / dry vacuum for solution pick up when floor drains are not available or are not in proper working order.

For large floor surface areas the use of an auto scrubber or floor machine will aid in deep cleaning. Always inspect conditions of grout line before cleaning.

SAFETY INFORMATION

Precautionary Statements – Prevention

Wash face, hands and any exposed skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statements – First Aid Measures

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs, get medical advice/attention. Take off contaminated clothing and wash it before reuse.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. Drink plenty of water.

IMPORTANT NOTICE: This product cannot eliminate slipping. Seller and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for the intended purpose, and the user assumes all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacturer. Buyer assumes all risks and liability associated with disposal. E. & O.E.