



Manufacturers and Distributors of Anti-Slip Treatments • Anti-Skid Coatings • Slip-Resistant Floor Care
• Anti-Slip FRP Panels & Step Covers • Safety Tapes • Anti-Slip Tapes

TECHNICAL DATA SHEET

FLEXSTRIP #8201 STRIPPER / FINISH REMOVER

DESCRIPTION & STRIPPING PROCEDURE

No Skidding Flexstrip is a precise chemical formulation that is a low odor, no ammonia added, finish remover. This high-performance product requires little dwell time for fast, effective and user-safe stripping action that rinses easy for floor finish application. Easily stripping floors has never been easier. Designed with Selective Implosion Technology, Flexstrip implodes the most fortified sealers and floor finishes on a molecular level. Polymer bonds are unlocked resulting in easy and safer finish removal.

Stripping Procedures

1. Dust mop or sweep floor to remove debris

Heavy Duty Stripping:

2. Dilute at 32 oz per gallon 1:4 (256 mL per liter) and apply to floor using a mop, followed by agitation.

• Room temperature tap water should be used for dilution

3. Pick up the stripping solution and residue using a wet vacuum or auto scrubber. Reapply stripping solution and agitate if needed. Allow for 10-15 min of dwell time. The use of a high productivity stripping pad is recommended

4. Thoroughly rinse floor with cold water to remove leftover residues from stripping. Flood coat the floor and let Neutralizer sit for 2-3 minutes. Thoroughly scrub rinse the floor with black/green pad.

5. Pick up the Neutralizer with a wet vac and then give the floor a clear water rinse with a mop or auto scrubber.

6. Allow floor to dry and apply floor sealer and/or finish.

PRODUCT CHARACTERISTICS

An effective neutral stripper for modern floor finishes and waxes.

- Paints, plastics, soft metals, hard metals, decorative metals, sealed wood and cork, stone cement, all types of tiles, marble, porcelain, brick, glass, rubber, linoleum, no-wax floors and other washable surfaces.
- Multi-purpose / Allows for economical dilution for all cleaning and degreasing applications.
- Free rinsing
- Neutral range pH / Safe on all types of water washable surfaces
- Does not dull or leave behind a residue
- Super concentrated

TECHNICAL DATA

Color	Pink
Odor	Pleasant
Actives (%)	18.2 ± 0.3
pH	9 ± 0.2
pH (Use Dilution)	7.4 ± 0.2
Upper Cloud	> 140°F
Lower Cloud	< 25°F
Flash Point	None
Hard Water	Stable
Biodegradable	Yes
Specific Gravity (gr/cc)	1.020 ± .002
Density (lbs/gal)	8.51 ± .015
Free Rinsing	Yes
Non-Corrosive	Yes
Shelf life	1 Year minimum in original unopened container

NOTICE: READ AND FULLY UNDERSTAND MSDS /SDS BEFORE USING.

IMPORTANT NOTICE: Seller and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for the intended purpose, and the user assumes all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacturer. Buyer assumes all risks and liability associated with disposal. E & OE

266 Wildcat Road, Toronto, ON Canada M3J 2N5

Phone: (416) 667-1788 Fax: (416) 667-1783 Toll Free: 1-800-375-0571 sales@noskidding.com www.noskidding.com