



Manufacturers and Distributors of Anti-Slip Treatments • Anti-Skid Coatings • Slip-Resistant Floor Care  
• Anti-Slip FRP Panels & Step Covers • Safety Tapes • Anti-Slip Tapes

## TECHNICAL DATA SHEET

### NO SKIDDING® EPICOTE ANTI-SLIP FLOOR COATING 79015-79033

#### DESCRIPTION

A solvent base anti slip coating for pedestrian traffic. Helps reduce the problem caused by slippery floor surfaces. Formulated for enhanced resistance to abrasion, moderate chemicals and water when compared to conventional coatings. May be used on interior and exterior concrete and metal steps, ramps, walkways, and similar surfaces.

#### PRODUCT CHARACTERISTICS

- ◆ Slip-resistant, coarse texture.
- ◆ Designed for heavy-duty pedestrian applications.
- ◆ Good resistance to water, oil, grease, and moderate chemicals.
- ◆ Very good wear and abrasion resistance.
- ◆ Suitable for interior and exterior use on concrete and metal surfaces.

#### SURFACE PREPARATION & APPLICATION INSTRUCTIONS

Apply to a clean, dry surface that is free of dirt, grease, waxes, chalking, soap build up, and loose paint. Age new concrete for a minimum of one month before painting. Concrete that is smooth troweled or treated with chemical "de-icers" should be acid etched with diluted muriatic acid then rinse very well with water and allowed to dry before coating to ensure adhesion. Bare metal must be correctly primed. Glossy surfaces Smooth concrete should be scuff sanded to promote adhesion.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

#### APPLICATION:

Stir thoroughly and apply without diluting with a low nap 3/8" roller at a spreading rate of 100 square feet per gallon. Spreading rate will vary depending upon surface texture and porosity. Do not apply if rain is expected or if the air or surface temperature will be below 50°F. Clean equipment immediately after use with mineral spirits and dispose of empty containers as per local environmental regulations. This product is not for use on surfaces subject to water or chemical ponding.

#### TECHNICAL DATA

Available Colors; 79015 Grey, 79017 Green, 79019 Tile Red, 79020 Safety Yellow, 79021 Black, 79022 Beige and 79033 Sand	Weight per gallon: 13 lbs/gal.
Viscosity: 94 KU average	Solids: 80% +/- 2.0
Volume Solids: 60% +/- 2.0	Flash Point: 104°F
Gloss: Mat (coarse texture)	Coverage: 100 sq. ft./gal.
VOC Content: Less than 340 g/l (2.8 lbs/gal)	Packing: 1 gallon and 5 gallon pails

**NOTICE: READ AND FULLY UNDERSTAND MSDS BEFORE USING.** This product is designed to help reduce the hazards of slippery areas – not prevent the hazards altogether.

**IMPORTANT NOTICE:** Seller and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for the intended purpose, and the user assumes all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacturer. Buyer assumes all risks and liability associated with disposal. This product cannot eliminate slipping. E & OE. 03/17

266 Wildcat Road, Toronto, ON Canada M3J 2N5

Phone: (416) 667-1788 Fax: (416) 667-1783 Toll Free: 1-800-375-0571 sales@noskidding.com [www.noskidding.com](http://www.noskidding.com)