



Manufacturers and Distributors of Anti-Slip Treatments • Anti-Skid Coatings • Slip-Resistant Floor Care
• Anti-Slip FRP Panels & Step Covers • Safety Tapes • Anti-Slip Tapes

TECHNICAL DATA SHEET

MAXIFLEX HT ANTI-SLIP GLOSS FLOOR FINISH #8703

DESCRIPTION

A durable gloss – high solids pure thermoplastic floor finish with anti-slip traction texture. This pure acrylic floor finish is produced in high pressure reactors using proprietary molecularly engineered polymers, the finest high pressure micronized wax emulsion, preservatives, leveling aids, interacted plasticizers and deionized water to offer a premium grade floor finish.

PRODUCT FEATURES & BENEFITS

- High solids formula/offers labor and material savings by limiting the number of wear coats which must be applied.
- Pure thermoplastic polymers.
- May be used with conventional or high-speed floor maintenance systems/Allows versatility and reduced inventory levels or additional products.
- hard wear surface, scratch and scuff resistant
- Designed for ease of application.
- Traction grit in product.

DIRECTIONS FOR USE

A premium quality high solids floor finish that provides a durable gloss in four applications with a slip resistant texture. Durable, detergent resistant, easy application, non-scuff, non-black marking and metal bonded for outstanding wear and appearance with a minimum of maintenance. Recommended for all floors.

Application of Finish: For best results seal terrazzo, concrete, cork and porous resilient tile floors before application of finish. Apply a thin uniform coat of finish in the conventional manner. Allow to dry for a minimum of 30 minutes after each coat. Do not apply more than four coats in a 24-hour period. Be sure to apply the anti-slip texture uniformly across the surface. Allow finish to thoroughly dry before allowing traffic on the floor. Provides outstanding beauty and gloss on sealed floors. If floor is unsealed or highly porous, additional coats may be required on the initial application. Please note this product is for vinyl, vinyl like surfaces, most stone surfaces, terrazzo. This product is not to be used on ceramic, porcelain, rubber or wood.

Maintenance: Maintain in the conventional manner by cleaning with a treated yarn dust mop to remove surface dirt daily. Damp mop or clean with an automatic scrubber as required, using an approved neutral cleaner at the specified dilution. Spray buffing to remove embedded soils is recommended. Worn areas, or the entire floor, may be re-coated as required to maintain a uniform high gloss. When stripping becomes necessary use an approved stripper for detergent resistant finishes.

SPECIFICATIONS

Type: Metal Bonded Integrated Polymer	Slip Resistance: U.L. Rated
Drying Time (minutes): 30	Freeze thaw stable: Yes. 3 cycles
Odor: Pleasant	Detergent Resistant: Yes
Color: White, opaque liquid	Gloss: Superior
Solids Content (%): 25±0.5	Durability: Superior
pH: 8.4±0.2	Soil Resistance: Superior
Coverage (sq. ft./gal): 2500	Scuff Resistance: Superior
Powdering: Nil	Black Mark Resistance: Superior
Film Appearance: Clear	Leveling: Excellent
Non-yellowing: Yes	Recoatability: Excellent
Flash Point: None	Removability: Excellent
	Shelf Life: 1-year minimum in original unopened container

SAFETY INFORMATION

CAUTION: MAY BE HARMFUL IF SWALLOWED. MAY CAUSE SKIN AND EYE IRRITATION. Avoid contact with eyes. Do not ingest. If ingested may cause severe gastric distress and blockage.

First Aid: For eyes: Flush thoroughly with water for at least fifteen minutes. If irritation persists, seek medical attention.

For Skin: Wash thoroughly with soap and water. If irritation persists, seek medical attention. **If ingested:** Do not induce vomiting. Give large quantities of water. Seek medical attention. Never give anything by mouth to an unconscious person. **KEEP FROM FREEZING. FOR PROFESSIONAL USE ONLY.**

IMPORTANT NOTICE: This product cannot eliminate the possibility of slipping. Seller and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for the intended purpose, and the user assumes all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacturer. Buyer assumes all risks and liability associated with disposal. E & OE 10/17