



Manufacturers and Distributors of Anti-Slip Treatments • Anti-Skid Coatings • Slip-Resistant Floor Care  
• Anti-Slip FRP Panels & Step Covers • Safety Tapes • Anti-Slip Tapes

## TECHNICAL DATA SHEET

### PASS ANTI-SLIP CLEAR COAT #8901

#### DESCRIPTION

PASS is a water-based indoor/outdoor hard surface sealer that provides superior resistance to moisture, grease, solvents and other foreign materials. Outstanding durability; coating will not whiten or “peel-off” surfaces. Ideal for concrete, terra cotta, brick, pavers, Saltillo tiles, as well as a wide variety of unglazed ceramic tiles.

#### PRODUCT FEATURES & BENEFITS

- Easy to apply/Saves time, labor and reduces training requirements.
- Fast Drying/Recoat quickly to save time
- UV Resistant/Great for outdoors or areas in direct sunlight.
- Low odor formulation/Excellent for both indoors and outdoors.
- Eliminates need for surface etching/saves time and labor
- Forms a wear resistant barrier on surface to grease, oil and soiling.
- Water resistant/Will not whiten or “peel-off” surfaces.

#### DIRECTIONS FOR USE

**Areas for Use:** Office buildings, manufacturing and industrial plants, shopping centers, mall, indoor/outdoor plazas, parking lots, auto repair shops/Dealerships, supermarkets and retail stores, schools & educational facilities, swimming pool surrounds, warehousing & storage facilities.

#### Floor Preparation for all interior/Exterior Surface

**Applications:** remove all grease, oil and other foreign materials from the surface. If previous coatings are present, remove the coating with appropriate stripper. Rinse the surface thoroughly and allow to fully dry prior to application of PASS.

**Application:** Please shake product to ensure integrated micro traction is evenly dispersed within container before using. Apply PASS using a rayon or other floor finish mop, lambs wool application or paint roller. Apply the first coat of PASS using a thin, even coating on surface. Allow a minimum of 45 minutes of drying time prior to application of additional coats.

**Routine Maintenance:** Damp mop floors with mop & bucket or clean with an automatic scrubber using appropriate neutral floor cleaner following label instructions. For areas that require heavy cleaning or degreasing, select appropriate degreaser cleaner following label directions. Rinse surface with water after cleaning.

#### SPECIFICATIONS

Color: White, opaque liquid	Freeze Thaw Stable: Yes (3 cycles)
Odor: Typical acrylic	Detergent Resistant: Yes
Non-volatile Solids (%): 22.0±0.5	Levelling: Excellent
pH: 8.25±0.25	Water Resistance: Excellent
Drying time (minutes): 30	Black Mark Resistant: Excellent
Coverage (sq. ft./gal) 2,500	Scuff Resistant: Excellent
Specific Gravity (gr/cc): 1.017	Resistant to Soiling: Excellent
Density (lbs/gal): 8.471	Gloss Retention: Excellent
Slip Resistant: Yes	Immediate Wet Look Gloss: Outstanding
	Shelf Life: 1 year minimum in original unopened container

#### SAFETY INFORMATION

**CAUTION:** MAY BE HARMFUL IF SWALLOWED. MAY CAUSE SKIN AND EYE IRRITATION. Avoid contact with eyes. Do not ingest. If ingested may cause severe gastric distress and blockage.

**First Aid:** For eyes: Flush thoroughly with water for at least fifteen minutes. If irritation persists, seek medical attention.

**For Skin:** Wash thoroughly with soap and water. If irritation persists, seek medical attention. **If ingested:** Do not induce vomiting. Give large quantities of water. Seek medical attention. Never give anything by mouth to an unconscious person.

Meets or exceeds 0.5 coefficient of friction as measured by James Machine Methodology ASTM D 2047-82.

KEEP FROM FREEZING. FOR PROFESSIONAL USE ONLY

**IMPORTANT NOTICE:** This product cannot eliminate the possibility of slipping. Seller and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for the intended purpose, and the user assumes all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacturer. Buyer assumes all risks and liability associated with disposal. E & OE

266 Wildcat Road, Toronto, ON Canada M3J 2N5

Phone: (416) 667-1788 Fax: (416) 667-1783 Toll Free: 1-800-375-0571 [sales@noskidding.com](mailto:sales@noskidding.com) [www.noskidding.com](http://www.noskidding.com)