



Manufacturers and Distributors of Anti-Slip Treatments • Anti-Skid Coatings • Slip-Resistant Floor Care  
• Anti-Slip FRP Panels & Step Covers • Safety Tapes • Anti-Slip Tapes

## TECHNICAL DATA SHEET

### FLEXFINISH LOW LUSTRE #8101

#### DESCRIPTION

An easy-to-maintain, durable slip-resistant floor finish that produces a satin gloss appearance. Ideal for use in assisted living/nursing centers, especially those that focus on Alzheimer's patients. Perfect for linoleum and other flooring where a high gloss appearance is not desired. Resistant to scuffing, scratching and black heel marks.

#### PRODUCT FEATURES & BENEFITS

- Low gloss appearance / Recommended for assisted living / nursing centers.
- Extremely durable finish / Reduces maintenance and wears exceptionally well.
- Self-sealing / does not require the use of a separate sealer.
- Designed for ease of application
- Slip-Resistant

#### DIRECTIONS FOR USE

**Floor Preparation:** Strip old finish and wax using Flexstrip and following label directions. If necessary, rinse thoroughly with clean water and allow to completely dry.

**Application:** Using a clean mop or applicator apply thin uniform coats of Flexfinish™ Low Luster Floor Finish. Allow to dry for a minimum of 20 minutes after each coat. Do not apply more than 4 coats in a 24-hour period. Floor should be thoroughly dry before traffic is allowed in area.

**Routine Maintenance:** Dust mop using mop treated with a dust mop treatment. Damp mop or clean with an automatic scrubber using Flexclean™ floor cleaner following label directions,

**Interim Maintenance:** Flexfinish™ Low Luster Satin Floor Finish is not recommended for burnishing. Scrubbing and recoating is recommended. Dilute cleaner in mop bucket according to label dilution directions. Liberally mop solution onto floor surface and allow to dwell for 1 to 4 minutes. Fill autoscrubber with clear water, mount scrubbing pad or medium grade brush. With vacuum off and squeegee up, scrub the floor until all embedded soils and scuffs are removed from finish. Lower squeegee and vacuum to remove all scrubbing solution, using clear water from the autoscrubber, rinse floor to remove any excess residue. Allow floor to completely dry prior to re-coating.

#### SPECIFICATIONS

Type: Metal Bonded Integrated Polymer	Anti-Slip: Yes
Coverage (sq. ft./gal): 2500-3000	Freeze thaw stable: Yes
Drying Time (minutes): 30	Detergent Resistant: Yes
Odor: Pleasant	Durability: Superior
Color: White, opaque liquid	Soil Resistance: Superior
PH: 8.2±0.2	Scuff Resistance: Superior
Powdering: Nil	Black Mark Resistance: Superior
Film Appearance: Clear	Leveling: Excellent
Non-yellowing: Yes	Recoatibility: Excellent
Flash Point: None	Removability: Excellent
	Shelf Life: 1 year minimum in original unopened container

#### SAFETY INFORMATION

**KEEP OUT OF THE REACH OF CHILDREN.**

**Precautionary statement**

**Prevention:** Observe good industrial hygiene practices.

**Response:** Wash thoroughly after handling.

**Storage:** Store away from incompatible materials

**Disposal:** Dispose of contents/container in accordance with local/regional/national/international regulations.

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR1910.1200.

**Additional safety measures:**

Read the entire label and SDS before using this product and for additional first-aid measures. Please email [customerservice@noskidding.com](mailto:customerservice@noskidding.com) For a copy of the SDS. KEEP FROM FREEZING

Meets or exceeds 0.5 coefficient of friction as measured by James Machine Methodology ASTM Method D 2047.

For Commercial and Industrial Use Only

**IMPORTANT NOTICE:** This product cannot eliminate the possibility of slipping. Seller and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for the intended purpose, and the user assumes all risk and liability whatsoever in connection therewith. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of seller and manufacturer. Buyer assumes all risks and liability associated with disposal. E & OE